


ART. 74

Gomiti 45° F/F, aisi 316 / A4

Elbows 45° F/F, aisi 316 / A4

Esecuzione: Microfusione

Execution: Microcasting



Codice Articolo <i>Item Number</i>	M <i>size</i>	DN/ID	l <i>(mm)</i>	Box	Master carton
00740001804	1/8"	6	17,7	5	/
00740001404	1/4"	8	18,6	5	/
00740003804	3/8"	10	20,5	5	/
00740001204	1/2"	15	22,5	5	200
00740003404	3/4"	20	25	5	/
00740010004	1"	25	28,2	5	/
00740011404	1"1/4	32	32,2	5	/
00740011204	1"1/2	40	36	5	/
00740020004	2"	50	42	2	/
00740021204	2"1/2	65	47	1	/
00740030004	3"	80	52	1	/
00740040004	4"	100	63	1	/

Filettatura: conforme a EN 10226-1 (EX ISO 7-1)

(filetto maschio conico, filetto femmina cilindrico)

Conicità 1:16 sul diametro

Angolo del filetto 55°

Pressione massima d'esercizio 150 lbs (Libbre) = 10,34 BAR PN10

Thread: according to EN 10226-1 (EX ISO 7-1)

(conical male thread, cylindric female thread)

Taper 1:16 on diameter

Angle of threads 55°

Maximum operating pressure 150 lbs = 10,34 Bar PN 10